

Hydraulic Harrow



Combination of
plane & notched disc



Gang lock



Hydraulic cylinder
with 4 ton capacity



Scraper



Gang angle lock



Bearing hub



Tyre locking system



Wider tubeless tyre
(optional) 10:0/75-15.3



BENEFITS

- Used in open field workings for the superficial ploughing, shattering of clods, preparation of soil for sowing, burial of organic substances & remains.
- To air the soil and to eliminate the weeds.
- It is designed to work in extreme conditions.

FEATURES

- Effectively break up heavy clods because of sturdy design and weight.
- High quality boron steel discs.
- Bearing spools for better lubrication and less load on tractor.
- It can be easily transported on the tyres using the hydraulic system.
- High quality seals are used to prevent the bearing & hub from mud & water entry.
- Maintenance is easy but needs to be scheduled.

SPECIFICATIONS

DESCRIPTION	FKHH-18	FKHH-20	FKHH-22	FKHH-24	FKHH-28	FKHH-32
FRAME (Inch)			5.2" x 5.2" x 7mm (T) Sq. pipe frame			
GANG BOLT (Inch)				1.6" (Solid Sq. Rod)		
NO. OF DISC	18	20	22	24	28	32
TYPE OF DISC			Notched or Plain Disc (as per customer requirement)			
DISC DIAMETER (Inch)				26" x 6 mm (T)		
WIDTH OF CUT (Approx)	6 ft. 10"	6 ft. 6"	8 ft. 2"	8 ft. 10"	10 ft. 2"	11 ft. 5"
DISTANCE BETWEEN DISCS				9"		
TYRE SIZE		7.50 X 16, 10.0/75-15.3 AW702 (8 TO 16 PR)				
BEARING HUBS	6			8		
WEIGHT (lbs. Approx)	2205	2502	2800	3077	4440	4704

