

Earth & Turf Topdressers

MODEL 320 VINEYARD SPECIAL **TOPDRESSER SPREADER**



-  **Slim 39-Inch Width Fits Between Narrow Rows**
-  **Special Side-to-Side Beater Provides Precise Spread**
-  **1 Cu. Yd. Capacity with Standard Loading Chutes**
-  **2 Cu. Yd. with Optional Light Material Sides (shown) for Fewer Loadings**

 **Earth & Turf Products, L.L.C.**
112 S. Railroad Ave. | New Holland, PA 17557

888-693-2638



Earth & Turf Topdressers

The Earth & Turf Model 320 Vineyard Special topdresser spreader features compact size with “slimmed down” frame and axle assembly to make it the perfect package for vineyards, orchards and row crops with extremely narrow rows.



Measuring only 39 inches in width, the Vineyard Special will fit perfectly between narrow vineyard rows, yet carries 1 cubic yard of topdressing. With optional light material sides, it can carry an impressive 2 cubic yards (maximum load weight 3,000 lbs.) to keep unproductive loading times to a minimum.

The Model 320 Vineyard Special features a specially designed side-to-side spread beater, to distribute material only to the left and right as the unit is pulled between rows. Its maximum spread width is 72 inches. An optional beater attachment assures an even spread of material across the rows. Beater and apron belt are driven by tractor hydraulics for maximum spreading flexibility.

SPECIFICATIONS

LOAD CAPACITY	1 cu. yd. / 0.8 m ³ 2 cu.yd. (w/light material sides) / 1.5 m ³
MAX. LOAD WEIGHT	3,000 lbs. / 1,361 kg
BOX WIDTH	34.5 in. / 87.6 cm 45 in. Including Flare (Light Material Sides) / 114.3 cm
BOX LENGTH	76.5 in. / 194.3 cm 89 in. Including Flare (Light Material Sides) / 226 cm
OVERALL HEIGHT	48.5 in Including Flare / 123.2 cm 56.5 in. Including Flare (Light Material Sides) / 143.5 cm
OVERALL WIDTH	39 in. / 99 cm
OVERALL LENGTH	122 in. / 309.9 cm
SPREAD WIDTH	Up to 72 in. / 183 cm
SPREAD SYSTEM	Standard Left-to-Right Beater
WEIGHT W/ TIRES	760 lbs. / 344.7 kg
TIRE SIZE	4 - 18.00 - 8.50 - 8
PROPULSION	Pull-Type
COMPONENT DRIVE	Tractor / Tow Vehicle Hydraulics
TOW VEHICLE MAX. POWER	24 hp / 18 kW
CONSTRUCTION	12 & 16 Gauge Bolted Steel, Industrial Powder Coat
OPTIONS	Wide-Spread Beater, Light Material Sides

