


FRESA CS

FALC[®]



FALC

SOLEX
320 S. Jefferson
Dixon, CA 95620
Tel: (707) 978-6633
www.solexcorp.com



40 - 70 HP



SERIE										
	HP	PTO	A mm.	B mm.	A inches	B inches	KG.	LBS	N.	
CS 1300	40 - 70	540	1340	1480	52,756	58,268	380	838	30	
CS 1500	40 - 70	540	1495	1635	58,859	64,371	400	882	36	
CS 1600	50 - 70	540	1585	1725	62,402	67,914	420	926	36	
CS 1800	50 - 70	540	1830	1970	72,048	77,560	450	992	42	
CS 2100	60 - 70	540	2090	2230	82,283	87,795	490	1080	48	

CS 4 = 4 VELOCITA'

- * **I** Velocità inserita * **D** Serierumdrehung
- * **F** Vitesse branchée * **E** Velocidad engranada
- * **GB** Inserted speed * **P** Velocidade engatada

P.T.O. 540 GIRI/MINUTO

● 18	● 19	● 20	● 21
○ 21	○ 20	○ 19	○ 18
173	194 *	214	237

CS 1 = 1 VELOCITA'

- I** Riduttore a 1 velocità (206 G/M)
- D** Untersetzungsgetriebe mit einem Gang (206 U/M)
- F** Réducteur avec 1 vitesse (206 T/M)
- E** Reductor a 1 velocidad (206 G/M)
- GB** 1 speed reducer (206 RPM)

FALC - Via Proventa, 41 - 48018 FAENZA (ITALIA) - e-mail: info@falc1960.com - www.falc1960.com

Numero nazionale:
Tel. 0546 29050
Fax 0546 663986

International number:
Tel. +39-0546 29050
Fax +39-0546 663986



Die technische Angaben die Merkmale und die Bilder sind wissend und verbindlich nicht dem Hersteller. - Los datos técnicos, las características y las ilustraciones son indicativas y no comprometen al constructor.

FALC s.p.a. - Via N. Sacco, 34 - FORLÌ - 022007 - 0101155511