






FREELAND

FREE LAND									
	mm.	Inches	Kg.	Pounds	N. denti	mm.	Inches	HP.	PTO.
2500	2858	112,520	2460	5424	16	350	13,780	110 - 180	540
3000	3188	125,512	2610	5754	18	350	13,780	130 - 180	540
3000	3188	125,512	2610	5754	18	350	13,780	130 - 200	1000
4000	4188	164,882	3230	7121	24	350	13,780	130 - 200	1000

- I Il FreeLand garantisce la capacità di operare in condizioni di estremo bagnato o di estremo secco, ottenendo una eccellente velocità ed una ottimale esecuzione del lavoro.
- F FreeLand garantie la capacité de travailler en conditions de sol extrêmement mouillées ainsi comme extrêmement secs, avec excellente vitesse et optimal résultat de travail.
- GB FreeLand allows to operate in extremely wet conditions so as extremely dry, obtaining a very good feed speed and optimal result.
- D FreeLand ersichert die Fähigkeit, in sehr bewässerten so wie sehr trocken Bedingungen zu arbeiten, und eine sehr gute Arbeitsgeschwindigkeit und Ausführung zu erreichen.
- E El FreeLand es un apero que garantiza un excelente trabajo a n en condiciones extremas, en terrenos muy h medos o muy secos, obteniendo una excelente velocidad y un ptimo trabajo realizado.
- PC FreeLand обеспечивает возможность работы в условиях очень влажной или очень сухой почвы, имея отличную скорость и оптимальное выполнение работы.

