

THREE SOLID PERFORMERS

Quality design, workmanship and materials have made our conventional bare root transplanters the proven leaders for over 65 years. These three models can plant over 50 plants per minute, depending on plant spacings.

Two operators feed the seedlings into rubber grippers which hold

and protect the plant as it is guided into the furrow. A variety of optional plant holders are available for different types of seedlings. There is also an optional holder for your small greenhouse cell plants. Field spacing adjustments are easily made by changing sprockets.

Quality designed for time proven results

MODEL 1500

Shown with optional polymer coated furrow opener, three point hitch, 55 gallon poly barrel and fiberglass seats.

When equipped with a 3 point hitch and 55 gallon barrel, the Model 1500 is the most economical and versatile single row planter available.



Shown coated

MODEL FWD1500

Shown with optional polymer coated furrow opener, rubber tire packing wheels, 55

gallon poly barrel, 3 point hitch and fiberglass seats.

The large front wheel drive tire eliminates sliding in dry, sandy and loose soil conditions by using the front wheel to power the planter.

Holland's 2-1/4" solid diamond shaped tool bar is available in 6 foot or 8 foot lengths. They are the recommended arrangement for use with 2 conventional units, which would not be needing fertilizer attachments. They include a CAT I or CAT II welded three point hitch.

