



Farm, Horticulture and Garden Equipment



Rotostone type RSE with rear roller.

For tractor from 80 to 160 HP



Standard Equipment

- 3-Point linkage cat. 2°.
- Single speed gearbox with 540 rpm PTO.
- Side transmission through reinforced chain Type ASA 140 HE.
- 4 blades each flange type Rotostone.
- Double frame made with special steel IMEX 700.
- Adjustable and self-cleaned selection grill.
- Rear bonnet adjustment with adjustable manual jacks.
- Rear perforated metal roller Ø 480 mm.
- Pin and hole adjustment roller.
- Cardan shaft with 4 discs clutch.
- <CE> Safety guards.

RSE									
Type	cm	cm	mm	N°	rpm (rotor)	Hp	mm	Kg	cm
145 RSE	145	185	540	28/42	240	80-100	480	1290	15/32
165 RSE	165	205	540	32/48	240	80-100	480	1340	15/32
185 RSE	185	225	540	36/54	240	90-100	480	1390	15/32
210 RSE	210	250	540	40/60	240	100-120	480	1510	15/32
230 RSE	230	270	540	44/66	240	110-130	480	1590	15/32
250 RSE	250	290	540	48/72	240	120-140	480	1680	15/32
270 RSE	270	310	540	52/78	240	130-150	480	1780	15/32
300 RSE	300	340	540	60/90	240	130-160	480	1900	15/32
320 RSE	320	360	540	64/96	240	130-160	480	2200	15/32
360 RSE	360	400	540	72/108	240	130-160	480	2400	15/32

