

# GENERAL PURPOSE AUGERS

## CS AUGER



### PARTS | Pilot Bits

**FISH-TAIL PILOTS:**  
25 = 2.5", 35 = 3.5"  
and 45 = 4.5"

ITEM		LBS	PART NO.
SB-25		.6 LBS	131740
SB-35		1.2 LBS	133402
SB-45		3 LBS	133407
SB-25 HF		.6 LBS	131740
SB-35 HF		2.1 LBS	133405
SB-45 HF		3.2 LBS	133410
SB-25 HFTC		1.4 LBS	132590
SB-35 HFTC		2.8 LBS	133406
SB-45 HFTC		3.2 LBS	133411
SB-25C		.3 LBS	132135
SB-35 C		1.2 LBS	133403
SB-45 C		3.1 LBS	133408
SB-25 CXC		1 LBS	132758



Pengo Pilots and Teeth are rated for drilling conditions that may or may not be applicable to your power source. Refer to the soil chart listed on page 2 of this catalog to determine which tooth type is right for the job.



Standard

Hardfaced (HF)

Hardfaced Tungsten Carbide (HFTC)

Carbide (C)

Carbide Tipped (CXC)

### FAS-N-LOK



35 Dirt

5T30

35HF

35HFF

5T30HF

### PARTS | Fas-N-Lok® Teeth

ITEM		LBS	PART NO.
35		.4 LBS	133835
5T30		.4 LBS	140029
35 HF		.6 LBS	140008
35 HFF		.6 LBS	140009
5T30 HF		.4 LBS	140014
35 C		.4 LBS	140007
5T30 C		.4 LBS	140012
1336L C		.6 LBS	140016
RB-5T30		.4 LBS	140013
RB-36LC		.6 LBS	140021



35C

5T30C

1336L C

RB-5T30

RB-36L C


#### DRIFT PUNCH

LBS | 1  
PN | 137750

For Easy Removal of Teeth Use this Drift Punch.

#### SOFT HAMMER

LBS | 3.5  
PN | 137737



For Easy Installation of Fas-N-Lok® Teeth Use a soft hammer to prevent breaking of tips.

### PARTS | Holders

#### T-35 HOLDER

LBS | 1  
PN | 171221



#### T-36 HOLDER

LBS | 1  
PN | 171231



### PARTS | Drive Lugs

#### 140 CS

LBS | 1  
PN | 151930



#### 140 S

LBS | .5  
PN | 151940



**GET ATTACHED!**  
The SB-25, -35 and -45 bits use the 140CS Pilot Bit Adapter PN 151930

**GET TOUGH!**  
Shipped with standard pilot and teeth, you may order additional upgraded hard-faced or carbide parts for your tough drilling conditions.