




SNOWBLOWERS PGS-740 & PGS-800

New semi-industrial snowblowers for tractors from 35 to 65 HP.

DESIGNED FOR TOUGH JOBS !

- Efficient in hard packed snow and ice, as well as in powdered snow.
- Weight on the tractor's 3 point hitch comparable to a Pronovost P-740.
- Chute on antifriction ring with gear driven rotation by hydraulic motor.
- Automatic double chain binder.
- Renold Chain #80HV in an oil bath.
- Best performance of the industry.



Specifications

Model	PGS-740	PGS-800
Recommended power	35 to 65 HP	
Approximate performance	500 imp. tons/hour (tractor 60 HP)	
Height of chute base	35"	
Chute rotation	On antifriction ring, hydraulic driven with motor	
Height of housing	36 3/4"	
Cutting height (lateral blades)	58 1/2"	
Working width	74"	80"
Drum diameter	28"	
Depth of drum	10 1/2"	
Drum position	Centered	
Drum liner	3/16" in Hardox 450	
Impeller blades	4 blades x 3/8" thickness - welded	
Size and height of impeller shaft	Diameter 1.575" (40 mm) - Height 18"	
Impeller speed	540 RPM (CW)	
Standard P.T.O. shaft	T60	
Auger	Double ribboned, welded, 28" diameter, toothed	
Drive chain	RENOLD No. 80HV in oil bath	
Shear bolt	1 for the impeller + 1 for auger	
Scraper blade	Carbon steel	Standard equipment
	Stainless steel	Optional
Skid shoes	Carbon steel (quick adjustment)	Standard equipment (2 skid shoes)
	Stainless steel (quick adjust.)	Optional (2 skid shoes)
	Rocktec (quick adjust.)	Optional (2 skid shoes)
Bearing / ductile iron casing	Standard equipment	
3-point hitch	Category 2	
Center of gravity from 3-pt hitch at its shortest	30 1/2"	
Rotational force (reference)	42 468 lb-in	44 580 lb-in
Weight*	1 475 lbs	1 526 lbs

Design and specifications subject to change without notice.

* Weight including chute, deflector cylinder and hydraulic motor for chute rotation.



Les Machineries PRONOVOST INC.
 260, Haut du Lac Sud, St-Tite,
 Quebec, Canada, G0X 3H0
 Tel.: (418) 365-7551 Fax: (888) 652-9270
 www.pronovost.qc.ca

Dealer:

Printed in Canada

2011/12