







PRE-PRUNING MACHINE CPL TOWER 1 PLUS WITH HOSES TO THE TRACTOR

Standard machine:

T1 PLUS FRAME	SAFETY	ON THE TRACTOR	
 - Hydraulic lifting cm 70 - Hydraulic tilting vertical frame +/-20° - Hydraulic side shift cm 60 - Manual tilting of the working head +/-15° - Electro-hydraulic opening with push button and locking - Quick connection PLUS 	Maximum pressure valve and flow divider motor Maximum pressure valve for opening Hydraulic stand for storage	- N.3 double-acting hydraulic distributors - N.1 single-acting hydraulic distributor - N.1 pressure free return - 25-35 Liter/min	
	В	В А	€

CODE MODEL	DISCS N.	В	В	А	€			
		cm min	cm MAX	cm				
6CPLT104NA	CPL T1 A 4+4	4+4	85	142	30			
6CPLT106NA	CPL T1 A 6+6	6+6	85	142	50			
6CPLT108NA	CPL T1 A 8+8	8+8	85	142	70			
6CPLT110NA	CPL T1 A 10+10	10+10	85	142	90			
6CPLT106GA	CPL T1 A 6+6 G (compac	t) 6+6	85	142	35			
6CPLT108GA	CPL T1 A 8+8 G (compac	et) 8+8	85	142	49			
6CPLT110GA	CPL T1 A 10+10 G (compac	t) 10+10	85	142	63			
CODE	Д	CCESSORIES				€		
"+ "	"+ " Price increase for hydraulic distributor 4+1 with levers for tractors without cabin							
"+E"	Price increase for electro-hydraulic controls with joystick 4+1 for tractors with cabin							
"+F"	Price increase for electro-hydraulic controls with joystick 7+1 for tractors with cabin							
4525001	Hydraulic tilting head +/- 15 ° (+1 movement)							
39989	Price increase for pair of finisching saw discs							

N.B. The standard machine is equipped with 3 hydraulic movements, it is possible to add 1 single hydraulic movement without replacing the hydraulic distributor or joystick 4+1.

NB: All models are equipped as standard with 1.5m-long hydraulic hoses from the coupling plate. For longer hoses a price increase of € 15,00 per meter per hose will be added.

