


Recommended optional and coupling frames pag 124-133



DOUBLE TRIMMER CRV VISION 2 L WITH BLADES WITH JOYSTICK 7+1

Standard machine:

V2 FRAME	SAFETY	ON THE TRACTOR
<ul style="list-style-type: none"> - Electro-hydraulic distributor with joystick 7+1 - Independent hydraulic lifting cm 60 - Vertical bars hydraulic tilting +/-15° - Hydraulic side shift cm 25+25, manual side shift cm 20+20 - Hydraulic tilting horizontal bars 90° - Manual adjustment horizontal bar height 35 cm 	<ul style="list-style-type: none"> - Maximum pressure valve and flow divider for motors - Spring safety for vertical bar - Spring safety for topping bar with closing for transport - Hydraulic stand for storage 	<ul style="list-style-type: none"> - N.1 single-acting hydraulic distributor - N.1 pressure free return - 25-35 Liter/min - 12 volt socket
		MOVEMENTS
		<ul style="list-style-type: none"> - 7 movements in use - 0 movements available

CODE	MODEL	BLADES NR	A	B	C	C	D	D	€
		A B	cm	cm	min cm	MAX cm	min cm	MAX cm	
6CRVV232LAF	CRV V2 A 3+2 F	3 2	105	75	120	210	170	280	
6CRVV241LAF	CRV V2 A 4+1 F	4 1	140	45	120	210	170	280	
6CRVV242LAF	CRV V2 A 4+2 F	4 2	140	75	120	210	170	280	
6CRVV251LAF	CRV V2 A 5+1 F	5 1	175	45	120	210	170	280	
6CRVV252LAF	CRV V2 A 5+2 F	5 2	175	75	120	210	170	280	
6CRVV253LAF	CRV V2 A 5+3 F	5 3	175	105	120	210	170	280	
6CRVV262LAF	CRV V2 A 6+2 F	6 2	210	75	120	210	170	280	
6CRVV263LAF	CRV V2 A 6+3 F	6 3	210	105	120	210	170	280	

CODE	ACCESSORIES	€
"G"	Price increase for Joystick 9+1 instead of 7+1	
33086	Right 1 blade bottom bar with manual tilting	
33086S	Left 1 blade bottom bar with manual tilting	
4509802	Hydraulic height adjustment of the horizontal bars 35 cm (only with joystick 9+1)	
33080	Right shoots conveyor for pruning machine	
33079	Left shoots conveyor for pruning machine	

Example: 6CRVV253LAF with joystick 9+1 = 6CRVV253LAG

