

Recommended Optional pag 152








CRF-X - PRUNING MACHINE FOR ORCHARDS

Standard machine:

FRAME	SAFETY	ON THE TRACTOR
- Proportional electro-hydraulic distributor with joystick 4+1 (for P4 model) - Proportional electro-hydraulic distributor with joystick 6+1 (for P6 model) - Hydraulic lifting 90cm - Column hydraulic tilting +/-15% - Hydraulic side shift 50cm and manual 25cm - Vertical bar with Ø 40cm discs	- Max pressure valve for motors - Stand for storage	- N.3 Double acting distributors (for hoses to the tractor model) - N.1 Single acting distributor - N.1 Pressure free return - 80 Liters/min - Socket 12V



CODE	MODEL	Α	€	
		cm		
6CRFX108A	Cutting bar with 8 discs with hoses to the tractor L=1,5m	270		
6CRFX110A	Cutting bar with 10 discs with hoses to the tractor L=1,5m	340		
6CRFX108AP4	Cutting bar with 8 discs and proportional joystick 4+1	270		
6CRFX110AP4	Cutting bar with 10 discs and proportional joystick 4+1	340		
NB combine bar with maximum 1 hydraulic movements total				
6CRFX108AP6	Cutting bar with 8 discs and proportional joystick 6+1	270		
6CRFX110AP6	Cutting bar with 10 discs and proportional joystick 6+1	340		

NB combine bar with maximum 3 hydraulic movements total

CODE	ACCESSORIES	+	€
32765	Adapter for mounting CRF-X on coupling frames for pruning machines (see pages 130-133)		
38102	Green pruning kit with support and 2 mobile knives to be mounted instead of the Ø 40cm disc	each	
10892	3 point coupling CAT 2 for tractors with front lift		

NB: For longer hoses a price increase of € 15,00 per meter per hose will be added

