



TRIMMER CRV VISION 2 PLUS U WITH BLADES WITH JOYSTICK 7+2

Standard machine:

V2 PLUS FRAME	SAFETY	ON THE TRACTOR
<ul style="list-style-type: none"> - Electro-hydraulic distributor with joystick 7+2 - Independent hydraulic lifting cm 60 - Independent hydraulic tilting vertical frame +/-20° - Hydraulic side shift cm 25+25 and manual side shift cm 20+20 - Manual height adjustment horizontal bar 35cm - Manual opening of U cutting bars - Manual tilting vertical cutting bars +/-11° - Independent motor controls - Quick connections PLUS 	<ul style="list-style-type: none"> - Maximum pressure valve and flow divider for motors - Spring safety for vertical bars - Safety joint spring for horizontal bars with closure for transport - Hydraulic stand for storage 	<ul style="list-style-type: none"> - N.1 single-acting hydraulic distributor - N.1 pressure free return - 70-80 Liter/min - 12V socket
		MOVEMENTS
		<ul style="list-style-type: none"> - 5 movements in use - 2 movements available

CODE	MODEL	BLADES NR		A	B	C	C	D	D	CLOSED MACHINE	€
		A	B	cm	cm	min cm	MAX cm	min cm	MAX cm	cm	
6CRVV232UAH	CRV V2 A U 3-2 H	3	2	105	75	130	220	200	290	215	
6CRVV242UAH	CRV V2 A U 4-2 H	4	2	140	75	130	220	200	290	215	
6CRVV243UAH	CRV V2 A U 4-3 H	4	3	140	105	130	220	200	320	215	
6CRVV252UAH	CRV V2 A U 5-2 H	5	2	175	75	130	220	200	290	215	
6CRVV253UAH	CRV V2 A U 5-3 H	5	3	175	75	130	220	200	320	215	
6CRVV263UAH	CRV V2 A U 6-3 H	6	3	210	105	130	220	200	320	215	

CODE	ACCESSORIES	€
"L"	Price increase for Joystick 9+2 instead of 7+2	
33080	Right shoots conveyor	EACH
33079	Left shoots conveyor	EACH
33086	Right 1 blade bottom bar with manual tilting	EACH
33086S	Left 1 blade bottom bar with manual tilting	EACH
45252	Hydraulic opening adjustment of vertical cutting bars (+2 movements)	
4509802	Hydraulic height adjustment of the top bars 35 cm (+2 movements)	

Example: 6CRVV252UAH with joystick 9+2 = 6CRVV252UAL

